

Data Sheet

LL01ED-ABXxxL06



■ Features& Typical Applications

- High efficiency
- Available in 2 beam Patterns
- Optimized for uniform effects
- Lens without Housing
- Stage Lighting
- Street Lights
- Decorative Light
- Architectural Lighting
- Down Light

■ Table of Contents


General Information & Product Nomenclature.....	P.2
Optical Specifications	P.3
Mechanical Specifications	P.4
Package Specifications	P.5

LL01ED-ABXxxL06

General Information

- Lens Material Optical Grade PMMA
- Operating Temperature range -40°C~+70°C(upper limit +80°C)
- Storage Temperature range -40°C~+70°C(upper limit +80°C)
 - * Average transmittance in visible spectrum 400nm~700nm>90%
- Usage and Maintenance:
 1. If necessary, clean lenses with mild soap, water and soft cloth.
 2. Never use any commercial cleaning solvents on lenses, like alcohol.
 3. Please handle or install lenses with wearing gloves, skin oils may damage lens or its optical characteristic.

Product Nomenclature







LL01ED-ABXxxL06

Optical Specifications



Xlamp MT-G 

Note: (1) degree: tolerance $\pm 2^\circ$
(2) optical value: tolerance $\pm 10\%$

Part Number	FWHM	Field Angle*	cd / lm	IES File
LL01ED-ABX24L06	20°	61°	3.8	Download
				
Beam Pattern	Light Distribution Curve	Illuminance Distribution		
Part Number	FWHM	Field Angle*	cd / lm	IES File
LL01ED-ABX38L06	38°	65°	1.8	Download
				
Beam Pattern	Light Distribution Curve	Illuminance Distribution		

*The Field Angle is the angle between the two directions opposed to each other over the beam axis for which the luminous intensity is 10% that of the maximum luminous intensity.

LL01ED-ABXxxL06

Mechanical Specification

1. Fixing method

Note: All dimensions are in mm.

☐ Glue


☐ Screw

☐ Tape

☒ Fixing-ring

☐ Frame


2. Lens dimensions



3. Lens + Leds+MCPCB assembly instruction




4. View assembly lens with MCPCB:





LL01ED-ABXxxL06

Package Specifications

Item	Quantity	Total	Size(L*W*H)	G.W
Inner box		9 pcs	26.4*26.4*2.8cm	64g
Outer box	63 pcs/box	63 pcs	29*29*22 cm	
Outer box				



9pcs/ box



63pcs/inner box



Note:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[LedLink Optics:](#)

[LL01ED-ABX24L06](#) [LL01ED-ABX38L06](#)